

Bosque Watershed, Texas 2D Base Level Engineering and Mapping Methods and Results

Texas Water Development Board Contract No. 1800012224, Task Order 10
FEMA MAS No. 27

November 2022

Prepared for:

Texas Water Development Board
Attn: Manuel Razo, GISP, CFM
1700 N. Congress Avenue
Austin, Texas 78701

Prepared By:

AECOM Technical Services
13640 Briarwick Drive, Suite 200
Austin, TX 78729
aecom.com

Document History

DOCUMENT LOCATION

K:/FY2021/21-06-0030S/Hydraulics - BLE|FY20|MAS 27|Bosque (12060203) - McLennan, TX 28/Hydraulic Data Capture - Hydraulic - BLE|FY20|MAS 27|Bosque (12070203) - McLennan, TX - 01

REVISION HISTORY

Version Number	Version Date	Summary Changes	Team/Author
1.0	August 2022	Draft Deliverable to TWDB	AECOM
2.0	November 2022	Final Deliverable to TWDB	AECOM

APPROVALS

This document requires the approval of the following persons:

Role	Name	Phone	Title (CLIN/RMC)	Review Date	Approved Date
Project Manager	Sean Sutton	512.457.7745	Project Manager	November 1, 2022	November 10, 2022

CLIENT DISTRIBUTION

Name	Title/Organization	Location
Manuel Razo	Contract Manager, TWDB	Austin, Texas

Table of Contents

1.	Introduction.....	1
2.	2D BLE Modeling Inputs and Controls.....	3
2.1	<i>Topographic Data.....</i>	3
2.1.1	Inventory.....	3
2.1.2	Evaluation.....	4
2.1.2.1	Bosque Watershed Source Terrain Data.....	5
2.1.3	Data Processing.....	5
2.1.4	DEM QA/QC.....	6
2.2	<i>2D BLE Methods.....</i>	6
2.2.1	2D Computational Mesh and Settings.....	6
2.2.2	Model and Boundary Condition Setup.....	7
2.2.3	Hydrology.....	8
2.2.3.1	Excess Precipitation for 2D Computational Mesh.....	8
2.2.3.2	Inflow Hydrograph Boundary Conditions.....	11
2.2.4	Hydraulics.....	13
2.2.4.1	Roughness Coefficients.....	13
2.2.4.2	Breaklines.....	14
2.2.4.3	Refinement Regions.....	15
2.2.5	Quality Control.....	15
3.	Results.....	15
3.1	<i>Calibration.....</i>	16
3.2	<i>Challenges.....</i>	18
3.3	<i>Recommendations.....</i>	19
4.	Floodplain Mapping and Effective Zone A Validation.....	19
4.1	<i>Special Flood Hazard Area.....</i>	19
4.1.1	Model Outputs.....	19
4.1.2	Methodology.....	19
4.1.3	BLE Flood Hazard Layer.....	20
4.1.4	Water Surface and Depth Grids.....	20
4.1.5	Additional 1-Percent Features.....	20
4.2	<i>Validation of Effective Zone A SFHA.....</i>	20
4.2.1	Initial Assessment A1 – Significant Topography Update Check.....	20
4.2.2	Initial Assessment A2 – Check for Significant Hydrology Changes.....	21
4.2.3	Initial Assessment A3 – Check for Significant Development.....	21
4.2.4	Validation Check A4 – Check of Studies Backed by Technical Data.....	21
4.2.5	Validation Check A5 – Comparison of BLE and Effective Zone A.....	21
4.2.6	Validation Results.....	22
4.3	<i>Flood Risk Analysis.....</i>	24
5.	References.....	26
	Appendix A BLE Map.....	27

List of Figures

Figure 1: Bosque Watershed.....	2
Figure 2: Bosque Watershed BLE Source Terrain Data	4
Figure 3: RAS6 2D Computational Mesh and Boundary Conditions and USGS Peak Streamflow Gages.....	7
Figure 4: Excess Precipitation Hyetograph Applied to 2D Mesh – Bosque	11
Figure 5: Inflow Hydrograph for Bosque – Inflow NB2	11
Figure 6: Inflow Hydrograph for Bosque – Inflow NB2 2	12
Figure 7: Inflow Hydrograph for Bosque – Inflow NB2 4	12
Figure 8: V-notch Breakline Approach at Bridge Crossing	14
Figure 9: Calibration Comparison.....	17
Figure 10: Bosque Watershed CNMS Validation Results	23
Figure 11: Ranking of Bosque Watershed HUC-12s	24

List of Tables

Table 1: FEMA Vertical Accuracy Requirements for Leveraged Data.....	4
Table 2: LiDAR Topographic Data Available for the Bosque Watershed.....	5
Table 3: USGS Peak Streamflow Gages.....	8
Table 4: Land Use(LU)-Soils-CN Matrix for Defining Initial Curve Number	8
Table 5: Rainfall-Runoff Curve Numbers.....	10
Table 6: Precipitation Totals estimated in HEC-HMS (post ARF).....	10
Table 7: Total Excess Precipitation Applied to 2D Mesh.....	10
Table 8: NLCD 2019 Manning's n Roughness Matrix.....	13
Table 9: Communities with 2D Mesh Refinement.....	15
Table 10: Effective and Model Base Flood Elevation(BFE) Comparison after calibration	16
Table 11: Calibration Results.....	16
Table 12: 1-percent Gage WSEL and RAS WSEL Comparison	18
Table 13: Peak Flows at the Location of Tie-in between North Bosque and Bosque.....	18
Table 14: Mapping Threshold Matrix	19
Table 15: Zone A Initial Assessment Results	21
Table 16: BLE Comparison Results.....	22
Table 17: Zone A Validation Results	22
Table 18: Hazus 5.1 Results for 1-Percent-Annual-Chance (100 year) Scenario.....	25

1. Introduction

Base Level Engineering (BLE) provides technically credible flood data for various geographies - community, county, watershed and/or state level. BLE data can be shared with Federal, State, local and tribal governments, this data sharing provides stakeholders at all levels the necessary data to make informed decisions to reduce future flood losses. Without the mapping of flood prone areas, there can be a lack of information to effectively communicate flood risk to community officials, citizens, and businesses.

BLE is a riverine hydrologic and hydraulic modeling approach that builds on lessons learned to produce a baseline understanding of flood risk to communities, produced to support the assessment and maintenance of the national flood hazard inventory. Engineering models are created during a BLE assessment, producing information that meets the mapping Standards for Flood Risk Projects (FEMA Policy Memo FP 204-078-1) to produce Zone A (1-percent-annual-chance flood) information. BLE data is intended to represent the base level of investment needed for all flood study efforts FEMA will undertake. The Bosque watershed BLE documented here was designed to use two-dimensional (2D) modeling techniques with enhancements and calibration to develop products that can be communicated and shared with stakeholders, and transitioned into FEMA regulatory data development workflows.

The intent of BLE is to provide communities technically credible flood hazard information in a cost efficient and timely manner. Additionally, BLE provides communities a chance to review draft modeling information, reflecting the potential changes in risk within their community. Providing additional flood risk datasets, like water surface elevation (WSEL) grids and flood depth grids, delivers alternative information that reinforces the variability of flood risk within a designated floodplain and supports historic community requests for a source to determine a Base Flood Elevation in Zone A areas.

For floodplain management purposes, BLE data may be used as best available information in areas that are designated as Zone A floodplain. It may also be used to regulate development in areas where no Special Flood Hazard Area (SFHA) has been mapped before. Communities may adopt BLE data to support local regulations, which facilitates use of the data in local floodplain management activities, including in the post disaster environment where a need for updated and/or enhanced flood hazard information may be necessary.

BLE provides information to communities who are currently unmapped and provides a digital entry to communities that are currently un-modernized. BLE acts as a measuring tool to allow FEMA to assess the current Zone A inventory identified as unknown or unverified in FEMA's Coordinated Needs Management Strategy (CNMS), which FEMA is required to evaluate once every five years, as described in Title 42 of the Code of Federal Regulations, Chapter III, Section 4101(e). FEMA makes this determination of flood hazard data validity by examining flood study attributes and change characteristics, as specified in the Validation Checklist of the Coordinated Needs Management Strategy (CNMS) Technical Reference. The CNMS Validation Checklist provides a series of critical and secondary checks to determine the validity of flood hazard areas studied by detailed methods (e.g., Zone AE, AH, or AO). While the critical and secondary elements in CNMS provide a comprehensive method of evaluating the validity of Zone AE studies, a cost-effective approach for evaluating Zone A studies has been lacking. Another important goal of the BLE process is scalability of the results, meaning that the model produced during the BLE assessment may be refined to produce a more enhanced model with additional manual correction and on the ground survey. If BLE modeling exists, FEMA will recommend that it be used as the base model for any detailed studies performed in those areas.

BLE practices leverage high-resolution topography that meets or exceeds the United States Geological Survey (USGS) 3-D Elevation Program (3DEP) standards and often applies flood engineering at a large scale as opposed to targeting stream reaches within a watershed. BLE can be conducted at any scale, commonly for larger areas (Hydrologic Unit Code (HUC)-8 watershed) but may be produced at the county or local level too. It is encouraged to do BLE for wider areas in order to build on efficiencies in modeling and ensure cost efficiency. Using current technologies, multiple watersheds or watersheds with large land areas can be analyzed at a more efficient rate to produce water-surface elevations and site-specific hazard data replacing outdated flood studies shown in existing Flood Insurance Rate Maps (FIRMs). All flood prone areas within a watershed will have an engineering model calculating multiple flood recurrence intervals and defining floodplains with elevation grids using high-resolution topography.

Per standard identification SID #84 and #133, BLE will include all recurrence intervals (0.2-percent, 1-percent, 1-percent plus, 1-percent minus, 2-percent, 4-percent, and 10-percent-annual-chance floods). As such, hydrologic and hydraulic analysis should be performed to determine the expected WSELs for each of the seven recurrence intervals previously identified.

The Bosque watershed 2D BLE project was scoped as described in the Texas Water Development Board (TWDB) Task Order 10. In an effort to increase and enhance the flood risk products in Texas, the study was contracted through the TWDB's Cooperative Technical Partner (CTP) program to AECOM Technical Services, Inc. This report documents the BLE process, products, and results for this watershed. Figure 1 depicts the Bosque watershed footprint.




Figure 1: Bosque Watershed

2. 2D BLE Modeling Inputs and Controls

Section 2 presents fundamental components required to execute a 2D hydraulic engineering analysis for the Bosque watershed. Inputs such as elevation data, hydrology from rain-on-grid and inflow hydrographs, and hydraulic analyses and variables are defined herein. HEC-RAS 6.1 rain-on-grid utility was applied in the production of the 2D BLE products produced for this watershed.

2.1 Topographic Data

A high resolution Digital Elevation Model (DEM) is a fundamental component for 2D engineering analyses by providing a detailed representation of the surface for hydraulic routing through the model area. As such, DEMs were developed for the Bosque BLE project by leveraging available high resolution gridded elevation data derived from Light Detection and Ranging (LiDAR) collections throughout the States of Texas. The 1-meter DEM developed to support the 2D BLE modeling and analysis, within the Bosque watershed, was executed using the following steps:

1. Available elevation data for the project area were inventoried and collected.
2. Leveraged elevation data were evaluated and prioritized based on source vertical accuracy, year of collection, and resolution.
3. Seamless DEMs were processed using Geographic Information Systems (GIS).
4. Quality was assured using quantitative and qualitative assessment.

Documentation regarding leveraged data including coverage, accuracy, acquisition dates, and source contact/agency are presented in the figures, tables and text within Section 2.1.2. All vertical accuracy specifications were obtained from the metadata or survey reports provided with the leverage datasets. All available metadata, survey reports, and other leverage documentation are included in the FEMA Data Capture Technical Reference compliant submittal content for the Bosque watershed.

2.1.1 Inventory

An inventory of existing topographic data was conducted for the Bosque BLE watershed footprint. Figure 2 depicts the datasets identified and leveraged across the project area. FEMA, National Oceanic and Atmospheric Administration (NOAA), USGS, Texas Natural Resources Information System (TNRIS) and other State and Federal agencies were queried to build the inventory with the most current and available data sources.




Figure 2: Bosque Watershed BLE Source Terrain Data

2.1.2 Evaluation

A data coverage assessment was conducted to check for data gaps, extent, accuracy, and completeness. A review of related documentation, reports, indexes, and metadata associated with the leveraged datasets ensured each dataset meets FEMA accuracy requirements for topographic data. Decisions to leverage or exclude a dataset (or portion of it), were based generally on the following criteria coupled with engineering judgment:

- Data meet FEMA vertical accuracy standards (Table 1)
- Date of origination
- Data density and coverage

Table 1 depicts the Risk MAP SID #43 vertical accuracy requirements based on flood risk and terrain slope within the floodplain being mapped.

Table 1: FEMA Vertical Accuracy Requirements for Leveraged Data

Level of Flood Risk	Typical Slopes	Specification Level	Vertical Accuracy*	LiDAR Nominal Pulse Spacing (NPS)
High (Deciles 1,2,3)	Flattest	Highest	24.5 cm / 36.3 cm	≤ 2 meters
High (Deciles 1,2,3)	Rolling or Hilly	High	49.0 cm / 72.6 cm	≤ 2 meters
High (Deciles 2,3,4,5)	Hilly	Medium	98.0 cm / 145 cm	≤ 3.5 meters
Medium (Deciles 3,4,5,6,7)	Flattest	High	49.0 cm / 72.6 cm	≤ 2 meters
Medium (Deciles 3,4,5,6,7)	Rolling	Medium	98.0 cm / 145 cm	≤ 3.5 meters
Medium (Deciles 3,4,5,6,7)	Hilly	Low	147 cm / 218 cm	≤ 5 meters
Low (Deciles 7,8,9,10)	All	Low	147 cm / 218 cm	≤ 5 meters

*Vertical Accuracy at 95% Confidence Level (FVA or NVA)/(CVA or VVA)

Table 2 depicts the complete list of source elevation data and attributes leveraged for the Bosque watershed. All datasets used for hydraulic analyses and mapping meet the highest specification level defined in Table 1. The following datasets were evaluated and prioritized as best available:

Table 2: LiDAR Topographic Data Available for the Bosque Watershed

Year	Description	Source/Owner	Accuracy ¹	Approximate Footprint (mi ²) ²
2017	2017 FEMA Region 6 TX – Brazos River QL2 LiDAR	FEMA	7.9 cm	433
2011	2011 TNRIS LiDAR: Bell, Burnet, and McLennan Counties	TNRIS	9.445 cm	220

¹RMSEz reported at the 95% confidence level

²Size of LiDAR DEM footprint utilized for BLE study

2.1.2.1 Bosque Watershed Source Terrain Data

The source elevation data for the Bosque watershed are DEMs derived from the 2017 FEMA Region 6 TX – Brazos River QL2 LiDAR; and the 2011 TNRIS LiDAR: Bell, Burnet, and McLennan Counties. Only points classified as “ground” points (i.e., bare earth) were imported from the LiDAR and used for development of the project DEMs. Bare-earth LiDAR data are typically made by filtering non-ground returns (e.g. buildings, vegetation, etc.) from the raw laser returns. Figure 2 depicts the extent of the data defined in Table 2.

2017 FEMA Region 6 TX – Brazos River QL2 LiDAR

The area covered by the Brazos portion of the Texas Red River FEMA Region 6 Lidar project includes the counties of Archer, Baylor, Bell, Bosque, Brown, Callahan, Coleman, Comanche, Coryell, Dickens, Eastland, Erath, Fisher, Hamilton, Jack, Jones, King, Knox, Lampasas, McLennan, Mills, Palo Pinto, Runnels, Shackelford, Stephens, Stonewall, Taylor, Throckmorton, and Young. The lidar aerial acquisition was conducted between January 1, 2017 and May 28, 2018. The horizontal datum for the data was NAD83 (CORS 2011) UTM Zone 14N with units in meters and the vertical datum is NAVD88 with the elevation units in meters realized with GEOID12B.

For the Brazos Basin Texas FEMA R6 Lidar Project, the tested RMSEz of the classified lidar data is 7.9cm.

2011 TNRIS LiDAR: Bell, Burnet, and McLennan Counties

The area covered by the 2011 TNRIS Lidar: Bell, Burnet, and McLennan Counties project is approximately 2,349 square miles and includes portions of Bell, Burnet, Coryell, Falls, Lampasas, and McLennan counties. The lidar aerial acquisition was conducted between March 11, 2011 and July 1, 2011. The horizontal datum of the data was NAD83 UTM Zone 14N with units in meters and the vertical datum of the data was NAVD88 with elevation units in meters realized with GEOID03. The lidar data tested at 9.445cm RMSEz.

2.1.3 Data Processing

ArcGIS software was utilized in order to create a digital surface model for the Bosque HUC-8 watershed project area. The LiDAR datasets were added to a mosaic dataset and prioritized by date with the most recent dataset taking the first priority. If two datasets are from the same year or flown at similar dates, the accuracy was reviewed to determine the priority. The mosaic dataset was exported to make a seamless bare earth DEM.

The exported DEM was reviewed through automated quality control (QC) to check for anomalies and outlier locations based on slope and cells that exceed z value differences from surrounding cells. Visual review was also performed to check for ground differences at the extents of the datasets for differences in ground values. The DEM did not originally account for the elevation around Lake Waco. The terrain was modified in Ras Mapper using a polygon layer to set the lake bottom elevation to match the lake’s conservation pool elevation, per Lake Waco data provided by Texas Water Development Board.

2.1.4 DEM QA/QC

DEMs developed for use in the Bosque watershed BLE analysis were developed and independently assured to meet quality standards of the project. The data were developed using a controlled process, were evaluated and assured by a topographic data development team, and were evaluated and assured by the engineering team. Quality assurance (QA) during the data development process includes, but is not limited to the following QC checks:

- Horizontal Projection Check
- Vertical Datum Check
- Resolution Check
- Format Check
- Seamless Data Check to ensure the DEM files are consistent and seamless along source data edges

The QC after the development process by the DEM development team included visual observations using hillshade, contouring, color rendering, and/or other visual aids to review and identify potential impactful anomalies within the DEM surface. This QC step included, but was not limited to the following QC checks:

- Seamless Data Check to ensure no voids along the edges and between the prioritized datasets
- NoData Value Check to ensure no null values
- Manual Elevation Check using hillshade rasters to find erroneous elevation issues
- Unit Consistency Check
- Legacy Cell Value Anomalies

QA conducted after the seamless DEM development conducted by the engineering team included visual or automated assessments to identify potentially impactful anomalies or slope changes that may adversely impact hydraulic analysis.

The final DEM data developed for the Bosque watershed is assured to meet FEMA standards and present a representative surface developed from leveraged elevation data for the purposes of this BLE project.

2.2 2D BLE Methods

HEC-RAS 6.1 (RAS6) rain-on-grid utility was applied in the Texas 2D BLE products workflow. The following sections describe the engineering methods and model inputs used.

2.2.1 2D Computational Mesh and Settings

The Bosque watershed is approximately 440 sqmi so the HUC-8 did not need to be clipped into smaller model areas. The HEC-RAS geometry is shown in Figure 3. The upstream boundary of the Bosque model area was adjusted to cross North Bosque River at a more upstream location from Lake Waco in order to avoid the model crossing in the middle of the lake and improve modeling efficiency. The RAS6 watershed boundary was created for the Bosque model area using ArcGIS toolsets, which reduce the need for manual edits to mesh cells within RAS6 that result in error generation. The Bosque 2D meshes contain 1,029,838 cells consisting of 200 foot cells, with the exception of 100 foot along the 1 square mile streams and 50 foot cells within community boundaries using refinement regions. Within community boundaries the streamlines were also extended to the 0.5 square mile extent and assigned 50 foot cell spacing in order to be more detailed. Internal connections were used to extract flow readings for gage locations throughout the model, while profile lines were used for all other flow extractions. An adaptive 30 second time step was used to allow the model to lower the time step, as necessary, to keep the maximum courant number under 1 for the duration of the simulation. The time step was allowed to reach 120 seconds for a maximum and 3.75 seconds for the minimum. The RAS6 model was run with Diffusion Wave (simplified Full Momentum) equations.

2.2.2 Model and Boundary Condition Setup

Using RAS6 rain-on-grid modeling requires a 2D computational mesh boundary and often requires defining inflow boundary conditions and application of excess precipitation. Excess precipitation was applied to the 2D mesh as a precipitation boundary condition. The process to determine the excess precipitation to be applied is outlined in the hydrology section. Figure 3 depicts the model boundaries, flow transition points between models, and USGS stream gages used in the study.

The outflows from multiple streams in the upstream model in North Bosque were used as inflow hydrographs for the Bosque work area. These hydrographs were extracted from the upstream model using a 2D connection, and then placed as either flow or stage hydrograph external boundary conditions for the Bosque model.

Outflow boundary conditions (from the computational 2D mesh) were used along model boundaries. Outflow boundaries were established as normal depth using approximate energy grade-line slope estimated from the LiDAR data. This allowed the boundary conditions defined as continuous boundaries to allow drainage to leave the model area freely to adjacent basins.




Figure 3: RAS6 2D Computational Mesh and Boundary Conditions and USGS Peak Streamflow Gages

2.2.3 Hydrology

Precipitation frequency data (NOAA, 2018) was used for this study. These data were obtained from NOAA's Precipitation Frequency Data Server (PFDS) (<http://hdsc.nws.noaa.gov/hdsc/pfds/index.html>), and appropriate values for all sub-basin elements were determined considering spatial variation and a representative total for the Bosque model area. Excess precipitation for the 2D mesh was developed as described in Section 2.2.3.1 USGS streamflow gage data were leveraged to estimate peak flows for downstream gages within each work area for calibration purposes, as discussed in Section 3.1. The 10-, 4-, 2-, 1-, and 0.2-percent annual chance 24-hour precipitation depths for all sub-basin elements were determined by area-weighted intersection of gridded PFDS data with sub-basins.

USGS streamflow gage data was leveraged to estimate peak flows for downstream gages within the model for calibration purposes. Model flows are compared to known USGS peak flows to validate the model results. USGS stream gages with less than 10 years of record were not considered for this study. The gages used for analysis in this study are listed in Table 3.

Table 3: USGS Peak Streamflow Gages

Gage ID	Flooding Source and Location	Published Drainage Area (mi ²)	Period of Record
08095300	Middle Bosque Rv nr McGregor, TX	182	1889-2021
08095400	Hog Ck nr Crawford, TX	78.2	1936-2021
08095600	Bosque Rv nr Waco, TX	1656	1916-1982

2.2.3.1 Excess Precipitation for 2D Computational Mesh

HEC-HMS version 4.8 was used to apply the Soil Conservation Service (SCS) Curve Number (CN) method to calculate losses and define excess precipitation for this watershed. Temporal distributions of point rainfall totals were defined using 24-hour, frequency-based storm distributions. The plus and minus standard error for the 1-percent annual chance precipitation depths were determined as the upper and lower 84% confidence limits on the nominal 1-percent depth, assuming a normal distribution of the logarithms for the precipitation depths. An areal reduction as per Technical Paper 40 (TP-40) was used in HEC-HMS on all recurrence interval total precipitation depths in order to determine the effective precipitation for the sub-basin representing 2D mesh.

In addition to recurrence interval precipitation estimates, NOAA Atlas 14 provides 90% confidence intervals of reported precipitation values. On a normal distribution curve, 90% confidence intervals (i.e. the upper and lower 95% confidence limits) correspond to +/- 1.645 standard deviations. The 1-percent plus and minus events are defined to be one standard deviation above and below the 1-percent event. It should be noted that the standard errors for the 1-percent rainfall depth were based on the depth used post-areal reduction. The estimated 1-percent plus and minus rainfall depths are shown, alongside the other events, in Table 6 later in this section.

Curve numbers were computed by intersecting the National Land Cover Dataset (NLCD) 2019 coverage and NRCS soils data based on the matrix presented in Table 4.

Table 4: Land Use(LU)-Soils-CN Matrix for Defining Initial Curve Number

LU_GridCode	NLCD LU Description	Hydrologic Soil Group			
		A	B	C	D
11	Open Water	99	99	99	99
21	Developed Open Space	49	69	79	84
22	Developed Low Intensity	61	75	83	87
23	Developed Medium Intensity	81	88	91	93
24	Developed High Intensity	89	92	94	95
31	Barren Land	39	61	74	80

Table 4, continued: Land Use(LU)-Soils-CN Matrix for Defining Initial Curve Number

LU_GridCode	NLCD LU Description	Hydrologic Soil Group			
		A	B	C	D
41	Deciduous Forest	30	55	70	77
42	Evergreen Forest	30	55	70	77
43	Mixed Forest	30	55	70	77
52	Shrub Scrub	30	48	65	73
71	Herbaceous	49	62	74	85
81	Hay Pasture	39	61	74	84
82	Cultivated Crops	51	67	76	80
90	Woody Wetlands	72	80	87	93
95	Emergent Herbaceous Wetlands	72	80	87	93

In addition to rainfall, the 1-percent plus and minus event estimates were further refined by adjustment of their respective CNs. A CN can be considered a parameter, exhibiting variability that follows some frequency distribution. While Antecedent Runoff Condition (ARC) II CNs were used for a 1-percent event, the range between ARC I and ARC III for the ARC II CN was assumed to correspond to an 80% confidence interval of the ARC II CN. The CN loss method assumes a maximum potential retention parameter, S, is inversely related to a CN by $S = 1000 / CN - 10$; this relationship is based on a median value of S determined from plotting a large number of observations.

Chapter 5 of the NRCS National Engineering Handbook (NEH) Part 630 provides an example of computing a CN for a watershed based on annual peak gage observations. The example involves computing a CN and corresponding S value for each event, then taking the logarithms of the S values. Further, the logarithm of S is assumed to vary normally, and the mean of the logarithms corresponds to the arithmetic median. Therefore, 10% (S10) and 90% (S90) extremes of lognormally distributed S values can be assumed to correspond to ARC III and ARC I condition CN values, respectively. This range represents an 80% confidence interval, corresponding to ± 1.282 standard deviations from the mean. The following procedure was used to estimate one standard deviation of a given CN (in fact, one standard deviation of the logarithm of S) for the purposes of modeling 1-percent plus and minus events. First, ARC III (corresponding to S10) and ARC I (corresponding to S90) CN values can be estimated from a 1-percent CN (ARC II) by:

$$CNI = 4.2 * CNII / (10 - 0.058 * CNII)$$

$$CNIII = 23 * CNII / (10 + 0.13 * CNII)$$

Next, S90 and S10 can be computed by:

$$S10 = 1000 / CNIII - 10$$

$$S90 = 1000 / CNI - 10$$

The following relationship can then be used to compute one standard deviation of the logarithm of S:

$$\log(S10) = \text{mean}(\log(S)) + 1.282 \text{ std. dev.}(\log(S))$$

$$\log(S90) = \text{mean}(\log(S)) - 1.282 \text{ std. dev.}(\log(S))$$

$$1 \text{ std. dev.}(\log S) = (\log S10 - \log S90) / 1.282$$

Therefore, 1-percent plus and minus S values can be estimated by:

$$\log S_{\text{Plus}} = \log S + [1 \text{ std. dev.}(\log S)]$$

$$\log S_{\text{Minus}} = \log S - [1 \text{ std. dev.}(\log S)]$$

Finally, 1-percent plus and minus CNs can be computed by:

$$CN_{Plus} = 1000 / (S_{Plus} + 10)$$

$$CN_{Minus} = 1000 / (S_{Minus} + 10)$$

Since the 1-percent plus and minus events represent plus and minus one standard deviation of a 1-percent event, CNs used in a rainfall-runoff simulation for modeling 1-percent plus and minus events were developed, as described above. A single basin was used in HEC-HMS for simulation to estimate excess precipitation.

Table 5 shows the curve numbers both initially computed and revised/verified values based on reasonability check revisions.

Table 5: Rainfall-Runoff Curve Numbers

Sub-basin Description	CN (initial)	CN (verified)	CN 1-percent Minus	CN 1-percent Plus
Bosque	80.45	70.0	54.6	81.9

NRCS rainfall-runoff methods were used to define excess precipitation applied to the 2D mesh, including CNs for defining rainfall losses. No routing was considered in the rainfall-runoff modeling. Frequency-based storm with 50% storm centering were used for-defining temporal distributions of point rainfall totals. Table 6 provides the precipitation totals applied to the model including areal reduction-factor (ARF).

Table 6: Precipitation Totals estimated in HEC-HMS (post ARF)

Percent Annual Chance Precipitation Depths (in.)							
Sub-Basin Description	1-percent	0.2-percent	2-percent	4-percent	10-percent	1-percent Plus	1-percent Minus
Bosque	8.71	11.74	7.60	6.59	5.32	10.46	6.96

Table 7 shows the excess precipitation totals determined from the HMS model. These values are a factor of the average CN and precipitation depths for each model area. Note that CNs were modified during the calibration process and the excess precipitation depths were recalculated to install confidence in the final model results.

Table 7: Total Excess Precipitation Applied to 2D Mesh

Percent Annual Chance Precipitation Depths (in.)							
Sub-Basin Description	1-percent	0.2-percent	2-percent	4-percent	10-percent	1-percent Plus	1-percent Minus
Bosque	5.08	7.81	4.12	3.28	2.28	8.20	2.06

Figure 4 shows the excess precipitation hyetograph used for Bosque. CN and precipitation depth are the two factors used by the HMS model to determine the magnitude of the excess precipitation event. The excess precipitation hyetograph is calculated in 6-minute increments.




Figure 4: Excess Precipitation Hyetograph Applied to 2D Mesh – Bosque

2.2.3.2 Inflow Hydrograph Boundary Conditions

Flows from multiple streams in the North Bosque model were used as inflows into the Bosque model. The inflow hydrographs were derived by utilizing the results of the HEC-RAS model for North Bosque directly upstream. The inflow hydrographs were extracted from the Bosque model using 2D connections. The inflow hydrographs applied to Bosque RAS model are represented in Figure 5, Figure 6 and Figure 7.




Figure 5: Inflow Hydrograph for Bosque – Inflow NB2




Figure 6: Inflow Hydrograph for Bosque – Inflow NB2 2




Figure 7: Inflow Hydrograph for Bosque – Inflow NB2 4

In order to achieve a seamless flood hazard result at a transition location (locations where flow is exchanged between 2D model areas), the water surface elevation (WSE) and inundation tie-ins between models must be made as close as possible. A 1,000 feet buffer was applied to each model work area for the mesh boundary. This is done so that the inflow boundary condition of the downstream model and the normal depth outlet boundary condition of the upstream model are far enough away from the work area transition location that they do not impact the WSE tie-ins between models in an undesired way. To make this overlap work without double accounting for rainfall, an internal 2D connection is placed in the upstream model at the exact same location as the inflow boundary condition for the downstream model. Approximately halfway between the model overlap is the actual model area boundaries where the mapped floodplain products switch from the upstream model results to the downstream model results. This transition location is the targeted area to have the water surface elevation and inundation tie-in as closely as possible.

2.2.4 Hydraulics

This section describes the remaining hydraulic modeling considerations, including implementation of Manning's roughness, breaklines, refinement regions, and hydraulic structures within the 2D computational mesh.

2.2.4.1 Roughness Coefficients

Manning's n roughness coverage was developed for the 2D computational mesh using typical roughness values for given NLCD land classifications. Two different sets of Manning's n values were used for areas within the channel and all other areas outside of the channels of the stream network. The channel layers were created using a 100 foot buffer. This allows for the model to accurately represent deep, swift flow within the channel and shallow overland flow outside of the channel areas. The table below shows a typical landuse-roughness matrix used in defining the roughness coverage for the study area for areas both inside and outside of the channel. In the HEC-RAS model Channel n values are listed as land classification – Channel, and Overbank bank n values are listed as land classification – Base.

Table 8: NLCD 2019 Manning's n Roughness Matrix

NLCD Classification	Channel			Overbank
	N Value	Source	N Value	Source
Open Water	0.03	Chow, 1959	0.03	Chow, 1959
Developed, Open Space	0.035	Chow, 1959	0.04	NRCS KS Dam Breach, 2016
Developed, Low Intensity	0.035	Chow, 1959	0.08	NRCS KS Dam Breach, 2016
Developed, Medium Intensity	0.035	Chow, 1959	0.1	NRCS KS Dam Breach, 2016
Developed, High Intensity	0.035	Chow, 1959	0.15	NRCS KS Dam Breach, 2016
Barren Land	0.03	Chow, 1959	0.03	NRCS KS Dam Breach, 2016
Deciduous Forest	0.05	Chow, 1959	0.16	NRCS KS Dam Breach, 2016
Evergreen Forest	0.05	Chow, 1959	0.16	NRCS KS Dam Breach, 2016
Mixed Forest	0.05	Chow, 1959	0.15	NRCS KS Dam Breach, 2016
Scrub/Shrub	0.04	Chow, 1959	0.1	NRCS KS Dam Breach, 2016
Grassland/Herbaceous	0.04	Chow, 1959	0.15	HCFC modeling Guidelines, 2018
Open Water	0.03	Chow, 1959	0.03	Chow, 1959
Developed, Open Space	0.035	Chow, 1959	0.04	NRCS KS Dam Breach, 2016
Developed, Low Intensity	0.035	Chow, 1959	0.08	NRCS KS Dam Breach, 2016
Developed, Medium Intensity	0.035	Chow, 1959	0.1	NRCS KS Dam Breach, 2016

2.2.4.2 Breaklines

Breaklines align grid cell faces and were used within the 2D mesh area to define prominent features including road embankments and hydraulic structures. Road embankment features were delineated in GIS and imported into RAS5 as breaklines to contain water where appropriate. Similarly, significant bridge/culvert crossings that were not processed out of the terrain data were modeled by v-notch breaklines adjacent to the road embankment to align grid cells around the embankment and allow water to be routed through the embankment without creating artificial backwater. An example of the v-notch breakline approach is shown in Figure 8.

County, interstate, common name, state recognized, and U.S. roads were incorporated for road breaklines from the U.S. Census Bureau TIGER/Line road layer.

There were three public dams in the modeling area. The two Hog Creek Sites were registered as being “low hazard” and were modeled with breaklines to show that they hold back water based on the terrain. However, the Waco Lake dam is considered “high hazard” and is too large to use only breaklines or a rating curve. Therefore, a 2D connection was used model the Lake Waco dam which is at the downstream of Bosque HUC-8. Data on the dam was gathered from the Texas Water Development Board and incorporated into the 2D connection to best represent the dam. All fourteen tainter gates were included in the 2D connection, as well as the ogee weir. Private dams were not modeled as showing protection. This is to lessen the burden on private dam owners to maintain their dams in order to sustain the regulatory products that could be created in the future as a result of this study. The study area does not include any FEMA accredited levees.

Breaklines were also used along all the stream centerlines of streams draining greater than one square mile of drainage area, and 0.5 square miles of drainage area within densely populated areas. Each streamline was topo-derived and the stream centerline was enforced with 100 feet cell spacing in order to align cells along the stream line and capture more detail along the one square mile stream network. Streamline alignment was also hand checked with the terrain by the modeler to ensure accuracy. Stream names were referenced from other sources such as NFHL and NHD datasets. In the HEC-RAS model, streams that passed through densely populated regions were enforced as breaklines using 50ft cell spacing.




Figure 8: V-notch Breakline Approach at Bridge Crossing

2.2.4.3 Refinement Regions

Refinement regions were created for each community within the model. The political boundary was used to determine the shape of the refinement region. Areas of the political boundary that lie within Lake Waco were clipped out of the refinement region. The regions were assigned a cell spacing of 50 feet by 50 feet. This finer cell spacing allows for more hydraulic calculations and mapping detail near areas where there are likely to be more structures. Table 9 shows the communities contained within Bosque watershed that were modeled with refinement regions as well as the square mileage of the refinement region.

Table 9: Communities with 2D Mesh Refinement

Community Name	Area (mi ²)
Crawford	1.09
McGregor	19.10
Waco	34.73
Woodway	6.40

2.2.5 Quality Control

The 2D BLE results were independently assured to meet quality standards of the project. Standard checklists complying with FEMA standards were used to review hydrology and hydraulics results, the resulting flood hazard area delineations and CNMS dataset. Quality assurance during the data development process includes, but is not limited to the following QC checks:

- Hydrological QC – included checks for curve number calculation, input precipitation, flood events, areal reduction factor and human error.
- Hydraulic QC – included checks for RAS geometry, breakline placement, v-notch placement to ensure water conveyance at crossings, refinement regions, roughness coefficients, boundary/initial conditions, timestep and mapping outputs
- Mapping – included checks for spot checking flood inundation accuracies based on floodplain mapping criteria described in section 4.1.2, ensuring flood extents from higher frequency events did not exceed lower frequency extents due to GIS smoothing algorithms, and topological overlap and cluster tolerance errors were resolved
- CNMS - Included review of the A1-A5 analysis for all effective approximate reaches in the HUC, geometry updates to newly studied reaches added as Zone X, and removal of scoped areas which lie outside of the final BLE footprint.

3. Results

The 2D BLE results for the study produced flood hazard area that compared reasonably well with effective SFHA in most cases, and provides additional estimated flood hazard risk area where not previously mapped. The HEC-RAS peak (max) results were exported for mapping and the HEC-RAS model was run with a hydrograph output interval of 1 hour, mapping output interval of 1 hour and the detailed output interval of 1 hour. The Bosque watershed is sufficient to facilitate FEMA regulatory processes while also providing the best available information for planning purposes. To further check the models accuracy additional profile lines were added and compared to Base Flood WSE that were available in the McLennan County Flood Insurance Study (FIS) dated December 20, 2019. The comparison is shown below in Table 10. The 2D BLE results should be verified through community work map meetings as part of the regulatory workflow.

Table 10: Effective and Model Base Flood Elevation(BFE) Comparison after calibration

Location Description	Effective BFE (feet)	Model BFE (feet)	Difference (feet)
Harris Creek Lower Stream at US Highway 84	553	549.21	-3.79
Speegleville Creek below US Highway 6	518	512.60	-5.40
Harris Creek Upper Stream at railroad	684	681.44	-2.56
Willow Creek at State Highway 317	671.9	676.12	4.22

3.1 Calibration

Known USGS gages within the model area with more than 10-years of flow record were used as the first priority for calibration of the 1-percent annual chance event. Discharges at gages were compared to discharges in the 2D models at the exact same locations. If a published rating curve was available, water surface elevations from the model were compared to the calculated 1-percent water surface elevations from the gage analysis.

Effective data was the second priority for calibration. Modeled flows were compared to flows from the summary of discharges tables from the McLennon County Flood Insurance Study (Effective December 2019). Known water surface elevations were used for validation, not calibration. Upper and lower limits for the effective flows were calculated by hand and were not taken from the FIS report. They were calculated by:

$$\text{Upper Limit} = 0.501 * 1\%Q$$

$$\text{Lower Limit} = 1.995 * 1\%Q$$

Two USGS gages that fall within the boundary of Bosque watershed were utilized for calibration purposes. Additional effective data was used for secondary calibration, but priority was given to the USGS gage analysis results. Adjustments to the CN value and to hydraulic features within the model were made until the flows in the model matched closely with the peak flows determined from gage and effective data. No adjustment to the n-values were made. Final results following model calibration at the calibration locations were presented in Table 11. The discharge from HEC-RAS model were calibrated with three USGS stream gages, and were within the specific range for all gages.

Table 11: Calibration Results

Calibration Location	Source	Method Used in Original Study	Reference			HEC-RAS 6.1 (2D) (cfs)
			Lower Limit (cfs)	1-percent (cfs)	Upper Limit (cfs)	
Gage 08095300	Middle Bosque Rv nr McGregor, TX	USGS	48,160	55,670	66,360	63,182
Gage 08095400	Hog Ck nr Crawford, TX	USGS	10,430	13,280	18,330	10,606
Gage 08095600	Bosque Rv nr Waco, TX	USGS	14,590	17,720	23,700	17,047

Table 11, continued: Calibration Results

Calibration Location	Source	Method Used in Original Study	Reference			HEC-RAS 6.1 (2D) (cfs)
			Lower Limit (cfs)	1-percent (cfs)	Upper Limit (cfs)	
Harris Creek Lower Stream at US Highway 84	McLennon County FIS	SCS W SP-2 Recurrence Intervals	6,882	13,736	20,590	10,492
Speegleville Creek below US Highway 6	McLennon County FIS	SCS W SP-2 Recurrence Intervals	2,320	4,630	9,237	1,958
Harris Creek Upper Stream at Railroad	McLennon County FIS	SCS W SP-2 Recurrence Intervals	8,876	17,717	35,345	7,366
Willow Creek at State Highway 317	McLennon County FIS	SCS W SP-2 Recurrence Intervals	938	1,872	3,735	1,530

Figure 9 shows the final results of the calibration locations compared to modeled flows throughout the Bosque watershed along with error bars created using the difference between 1-percent and 1-percent plus discharges and 1-percent and 1-percent minus discharge as minimum and maximum values. Seven comparisons were made with varying drainage areas to ensure the calibration of excess precipitation for different points over the entire watershed area. This large collection of calibration points provides confidence in results throughout the entire watershed. Because the Bosque model drains into Lake Waco that lies along the Bosque River in the middle of McLennon County, it is likely that the discharge is affected by the backwater of the lake and more detailed investigation into the impacts of the lake backwater and correlation with the modeling may be warranted in the future.




Figure 9: Calibration Comparison

The WSEL from the HEC-RAS model was validated using two USGS stream gages, gage 08095300 and 08095400. Based on the published rating for the USGS gage, a 1-percent gage WSEL was calculated, along with upper and lower WSELs bounds, using the 1-percent flow estimated by the gage analysis. These were compared to the WSEL at the same location in the Bosque model, as shown in Table 12. The modeled WSEL fall within the acceptable range of gages 08095300 and 08095400.

Table 12: 1-percent Gage WSEL and RAS WSEL Comparison

USGS Gage ID	Lower Bound (feet)	Gage WSEL 1-percent (feet)	Upper Bound (feet)	HEC-RAS 6.1 WSEL (feet)
08095300	557.66	558.77	560.22	560.21
08095400	572.78	574.20	576.37	575.84

With terrain modification and several modeling iterations, multiple changes were made to the downstream Bosque model and the upstream model of North Bosque 2, to create a reasonable tie-in and an effective WSE for Lake Waco. The Bosque 1PAC model was initially run and calibrated for gage flows and the WSE of the lake using inflows directly from the upstream model. In the mainstem and surrounding areas, the inflow was significantly low to create a high enough WSE to tie in with the effective data. A gage transfer for the mainstem inflow was tested and linear interpolation was used to interpolate values from USGS gage 08095200 to the location of the model transition. The mainstem inflow was multiplied by a factor of 1.122, which allowed the flows to peak at the value of the gage transfer while the hydrograph kept the same shape as the North Bosque 2 outflow, resulting in the lake WSE to raise to the target value of 500 feet. The Bosque results were then exported back into North Bosque 2 as a stage hydrograph for the downstream boundary condition at the mainstem outlet and the North Bosque 2 model was run again. This resulted in having a perfect tie-in between the models and meeting the target WSEL for the lake.

The gate operations of Waco Dam in the Bosque model create a backwater effect that impacts the flows in both models. It was tested that without this iteration the direct flow transfer from North Bosque to Bosque was not enough to raise the lake level. When using a stage hydrograph to raise the lake WSE, the North Bosque model doesn't require as much flow to get to the target WSE in Bosque since there is existing water in the channel that is not flowing but still contributing to the WSE. This also results in a difference in peak flows at the flow transfer location, and peak flows in North Bosque tend to be less than in Bosque as shown in Table 13. Considering the backwater effects in the lake a flow discrepancy is expected and the results of the models are acceptable in the current scope.

Table 13: Peak Flows at the Location of Tie-in between North Bosque and Bosque

Model	1PAC Flow (cfs)	WSE of Lake (feet)
Bosque	164,406	500.02
North Bosque 2	141,963	500.02

3.2 Challenges

The outflow from the upstream model containing the Bosque River was used as an inflow boundary condition to the downstream model, requiring tie-in and coordination between the two model areas. The Bosque watershed contains several dams. The Hog Creek dams were modeled using breaklines. The Waco Lake Dam at the outlet of Waco Lake was modeled using a 2D connection to input the structure. Data from the Texas Water Development Board was used to add the structure to the model. Due to the project scope, structure survey data was not included in this analysis, therefore many default variables were used for this structure. The HUC-8 also included a large urbanized area. All of this created extended run times for the model. The dam also brought along challenges with the tie-in

between the Bosque model and the upstream North Bosque model. Backwater effects caused the lake in Bosque to be lower than expected, but with modifications to the terrain and boundary conditions in the upstream model, the tie-in was able to be improved and acceptable.

Within the watershed, there are several populated areas and agricultural fields that appear to be trapping water which prevents runoff from reaching the channel in the model. Various v-notches were applied to represent cross culverts and improve conveyance. Further detail and study of the flow patterns and likely runoff conveyance would be recommended as part of a future study if more detailed flood risk information was needed in these areas.

3.3 Recommendations

This study provides significant information useful for flood identification and communication among those affected. The study is highly scalable, and stakeholder input and further analysis would enhance the product and inform implementation of regulatory flood hazard areas. In addition, the validity of the 2D BLE results should be verified through community work map meetings before being applied as a regulatory product. Further detailed analysis around Lake Waco is warranted also warranted.

Point source Atlas 14 rainfall was used in the analysis, and due to the large size of the modeled area (the entire HUC-8 watershed), the point rainfall used has a tendency to vary more widely from the actual point rainfall data at any specific location within the watershed. For detailed modeling and further improvements, smaller-sized modeled areas are recommended, which will result in smaller rainfall and CN variability. In addition, future versions of HEC-RAS are anticipated to include the capability to utilize spatially varying rainfall, which may result in additional improvements in the reasonability in some of these aspects. The hydraulic model can further be improved by using a smaller cell size than 200 foot along with adding structural and survey data for each crossing.

4. Floodplain Mapping and Effective Zone A Validation

The following sections provide a synopsis of how raw modeled depths were translated into SFHA. In addition to developing a new SFHA, the BLE model data was leveraged to validate the effective Zone A studies within the project footprint.

4.1 Special Flood Hazard Area

4.1.1 Model Outputs

The HEC acknowledged RAS Mapper may not render water surface elevation values and/or delineate inundation extent appropriately for direct use in FEMA regulatory mapping products. To maintain a high level of consistency between modeling results and final mapping, minimal map clean up was performed while maintaining identification of both fluvial and pluvial flood risk as reflected by the models. Additional processing may be required to make the mapping products FEMA compliant.

4.1.2 Methodology

The sloping render mode plots water surface elevation (WSE) by interpolating the WSE between the 2D cell faces, producing a more continuous flood inundation extent. Depth rasters from the sloping render mode were exported for the 10-percent, 1-percent, and 0.2-percent flood events with a tolerance of 0.001 feet. To reduce the extent of disconnected flood areas, raster grid processing is used to filter and remove disconnected, small, or shallow areas of flooding by processing through the 'Mapping Threshold Matrix' shown in Table 14.

Table 14: Mapping Threshold Matrix

Area (acres)	Average Depth (feet)
< 0.33	-
0.33 – 0.5	< 0.5
0.5 – 1.0	< 0.33
1.0 – 2.0	<0.1

Polygon outputs from the 'Mapping Threshold Matrix' also fill in minor areas of high ground (islands) that are less than 0.33 acre. The outputs are then modified through a Simplification and Smoothing process to reduce unnecessary/erroneous vertices, remove rough edges and reduce the size and complexity of the raw floodplain polygons for the 1-percent, and 0.2-percent flood events. For the North Bosque watershed, the polygon outputs were simplified by retaining critical points at a 5 foot tolerance. The simplified polygon outputs were then smoothed utilizing the PAEK algorithm and the tolerance was set to 25 feet. The 10-percent flood event polygons are not modified through the simplification and smoothing process and are delivered in the rasterized polygon shape.

Due to topographic differences within a lake footprint, these areas sometimes appear partially mapped in the flood extents from the model results. Lakes and reservoirs larger than 40 acres are reviewed to ensure full inundation on the 1-percent, and 0.2-percent polygon extents. If necessary, lake boundaries were copied into the flood event polygons to make sure they are fully mapped.

Once the final polygon flood extents are complete, it is necessary to merge the 10-percent boundaries into the 1-percent and the 1-percent extents into the 0.2-percent extents. This step ensures that the extents of the 10-percent floodplain is smaller than the 1-percent floodplain, and the 1-percent is smaller than the extents of the 0.2-percent floodplain.

4.1.3 BLE Flood Hazard Layer

BLE database format FLD_HAZ_AR feature classes were developed and attributed with Zone A and Shaded Zone X features. The BLE FLD_HAZ_AR feature class was tested for topological errors described in the FIRM Database Technical Reference and all errors were fixed for data integrity and schema agreement. The 10-percent boundaries have been included in the BLE TENPCT_FP feature class.

4.1.4 Water Surface and Depth Grids

Once the final floodplain polygons were created, it is required that the depth and WSEL grids match the full extents of the flood inundation polygons. Because of the processing of the floodplain polygon boundaries through the above mentioned steps, there are areas in the model produced raster grids that no longer match the polygons. Final grids are interpolated for areas filled in with surrounding cell values and then clipped to the polygon extents to create the final water surface and depth grids for the 1-percent and 0.2-percent flood events.

4.1.5 Additional 1-Percent Features

The BLE results for this study produced a SFHA that compares favorably with the effective SFHA. These boundaries provide an estimated SFHA in areas that have not been previously studied and therefore do not currently have an SFHA mapped. These results provide context for flood risk communication as part of the Discovery process, and should be verified through community work map meetings before being applied to a regulatory product.

A map showing the BLE results is included as Appendix A BLE Map.

4.2 Validation of Effective Zone A SFHA

The inventory of Zone A studies (293.5 miles) in the Bosque Watershed were classified in CNMS with validation status of "UNVERIFIED" (57.9 miles) or "VALID" (235.6 miles), and with status type of "BEING STUDIED." The following is a summary of the results of the CNMS validation assessment for the effective Zone A studies in the study area. Initial Assessment checks A1-A3 were evaluated for the CNMS inventory of Zone A studies.

4.2.1 Intial Assessment A1 – Significant Topography Update Check

This check involves determining whether a topographic data source is available that is significantly better than what was used for the effective Zone A modeling and mapping. For the study area within Bosque Watershed, LIDAR sources were not used for the effective study. LIDAR sources are now available in this area and are considered significant improvements from the effective zone A topographic sources. Therefore, reaches within this study area fail this check.

4.2.2 Initial Assessment A2 – Check for Significant Hydrology Changes

This check involves first determining if regression equations were used for the effective study. Next, it must be determined whether new regression equations have become available from the USGS since the date of the effective Zone A study. If newer regression equations exist for the area of interest, then an engineer must determine whether these regression equations would significantly affect the 1-percent annual chance flow.

For zone A streams within McLennan County, 2001 regression equations were utilized. New regression equations were published for the area in 2009 (SIR 2009-5087), creating a significant change in discharge. A2 fails for all reaches in McLennan County as a result. For all other Zone A streams within Bosque Watershed, regression equations were not known to be used for any effective studies and, therefore, pass this assessment check.

4.2.3 Initial Assessment A3 – Check for Significant Development

This check involves using the National Urban Change Indicator (NUCI) dataset to assess increased urbanization in the watershed of the Zone A study. If the percentage of urban area within the HUC-12 watershed containing the effective Zone A study is 15% or more, and has increased by 50% or more since the effective analysis, the study would fail this check. Although the NUCI data provide year-to-year changes in urbanization, the NLCD also is needed to establish a baseline of urban land cover for this analysis. The check for significant development in this watershed was completed by evaluating percentage of urban change at the HUC-12 level. All effective studies in the Bosque HUC-8 are in rural watersheds and, therefore, pass this check for that reason.

All of the initial assessment results are shown in Table 15.

Table 15: Zone A Initial Assessment Results

Assessment Check	Pass / Fail	Notes
A1 – Topography	Fail	Effective Study did not utilize LiDAR source and LiDAR is now available.
A2 – Hydrology	Pass/Fail	Regression equations not used in effective/New equations have been published since those used in the effective study
A3 – Development	Pass	Watershed does not meet urban threshold

4.2.4 Validation Check A4 – Check of Studies Backed by Technical Data

Zone A studies that pass all initial assessment checks described above may be categorized as “Valid” in the CNMS Inventory only if the effective Zone A study is supported by modeling or sound engineering judgment and all regulatory products are in agreement. If the effective Zone A study passes all initial assessment checks, but is not supported by modeling, or if the original engineering method used is unsupported or undocumented, a comparison of the BLE results and effective Zone A's is performed. No Zone A studies in the Bosque HUC-8 are known to be model-backed and fail this check.

4.2.5 Validation Check A5 – Comparison of BLE and Effective Zone A

The BLE /effective Zone A comparison method leverages the existing Floodplain Boundary Standard (FBS) certification procedures described in FEMA SID 113, but with a slight modification. This modified FBS comparison approach uses the 1-percent plus and 1-percent minus flood profiles and horizontal and vertical tolerances described in FEMA's Automated Engineering guidance document dated May 2016. For the comparison of BLE and effective Zone A in the Texas study area, the following vertical and horizontal tolerances were used to conduct the modified FBS procedure. One point was placed every 200 feet along the floodplain boundaries for comparison.

- Vertical Tolerance: +/- 5 - 10 feet (one-half contour interval of effective topographic source).
- Horizontal Tolerance: +/- 75 feet (standard horizontal tolerance for BLE comparison testing).

Comparison results for these streams were grouped at the HUC-12 level and are summarized in Table 16 to better understand the general health of the HUC-12 watershed, but the validation check was performed at the stream level. Streams where the percentage of passing FBS sample points is greater than or equal to 85% are marked as "Pass", otherwise marked as "Fail".

Table 16: BLE Comparison Results

HUC-12 Watershed		Total FBS points	Fail	Pass	%Pass	BLE Comparison Pass? (>85%)	Priority Score
Watershed Name	Watershed Number						
Bosque Watershed	All Streams	18,452	1,806	16,646	90%	Pass	
Harris Creek-South Bosque River	120602030302	1,721	163	1,558	91%	Pass	8.1
Headwaters Middle Bosque River	120602030101	1,297	124	1,173	90%	Pass	4.8
Lower Hog Creek	120602030202	1,980	186	1,794	91%	Pass	4.6
Lower Middle Bosque River	120602030105	2,852	255	2,597	91%	Pass	4.5
Middle Middle Bosque River	120602030103	1,604	269	1,335	83%	Fail	8.4
Tonk Creek	120602030104	1,891	121	1,770	94%	Pass	3.2
Upper Hog Creek	120602030201	2,063	202	1,861	90%	Pass	3.4
Upper Middle Bosque River	120602030102	850	61	789	93%	Pass	3.2
Waco Lake-Bosque River	120602030303	640	223	417	65%	Fail	13.5
Willow Creek-South Bosque River	120602030301	3,554	202	3,352	94%	Pass	3.3

4.2.6 Validation Results

Based on the validation assessments and BLE comparison results described above, the CNMS inventory of Zone A studies in the Bosque watershed has been updated as summarized in Table 17 and illustrated in Figure 10.

Table 17: Zone A Validation Results

Validation Status	Status Type	Total Miles
VALID	BEING STUDIED	235.6
UNVERIFIED	BEING STUDIED	57.9




Figure 10: Bosque Watershed CNMS Validation Results

An overall risk for each HUC-12 watershed was calculated using the National Flood Risk Percentages Dataset and its proportional area. The weighted risk was multiplied by the percentage of points in the watershed that failed the CNMS comparison to effective to determine the priority score. Figure 11 below shows the range of the HUC-12 priority scores which can be used to initiate discussions during the Discovery phase.

Waco Lake-Bosque River HUC-12 was determined to have the highest priority score and the most need while Tonk Creek and Upper Middle Bosque River HUC-12's had the lowest score.




Figure 11: Ranking of Bosque Watershed HUC-12s

4.3 Flood Risk Analysis

A flood risk analysis was performed for this project. The updated 1-percent annual chance depth grid was used to calculate the potential flood losses. The loss results are stored in the S_FRAC_AR spatial file within the FRD geodatabase. All results are reported in whole dollar values.

Hazus version 5.1 was used for the loss analysis.

The losses are reported via census blocks. It is important to note that Hazus version 5.1 uses dasymetric census blocks. Dasymetric mapping removes undeveloped areas (such as areas covered by other bodies of water, wetlands, or forests) from the census blocks, changing their shape and reducing their size in these areas. For more information on dasymetric data visit FEMA's [Media Library](#) for the [Hazus-MH Data Inventories: Dasymetric vs. Homogenous](#), or [Hazus 3.0 Dasymetric Data Overview](#).

Hazus analysis was performed by watershed extents for the 1-percent annual chance event to ensure proper model processing. A summary of results for counties within the watershed for the 1-percent annual chance scenarios are shown in Table 18. Totals only reflect data for those census tracts/blocks included in the user's study region and will reflect the entire county only if all of the census blocks for that county/state were selected at the time of study region creation.

Table 18: Hazus 5.1 Results for 1-Percent-Annual-Chance (100 year) Scenario

County	Full Replacement – Total Loss	Dollar Exposure (Replacement Value) - Buildings	Dollar Exposure (Replacement Value) - Contents
Bosque	\$586,000	\$19,933,000	\$10,328,000
Coryell	\$3,543,000	\$119,346,000	\$63,931,000
Hamilton	\$5,000	\$155,000	\$77,000
McLennan	\$322,311,000	\$5,629,390,000	\$3,583,454,000
Total	\$326,445,000	\$5,768,824,000	\$3,657,790,000

5. References

FEMA, *McLennan County Flood Insurance Study, Texas*, December 2019

Harris County Flood Control District – TX, *Two Dimensional Modeling Guidelines*, July 2018

Homer, C.G., Dewitz, J.A., Yang, L., Jin, S., Danielson, P., Xian, G., Coulston, J., Herold, N.D., Wickham, J.D., and Megown, K., 2015, *Completion of the 2016 National Land Cover Database for the conterminous United States-Representing a decade of land cover change information. Photogrammetric Engineering and Remote Sensing*, v. 81, no. 5, p. 345-354

National Oceanic and Atmospheric Administration. NOAA Atlas 14, Volume 11 Version 2.0 Texas, *Precipitation-Frequency Atlas of the United States*. Silver Spring, Maryland, 2018.

Painter, C.C., Heimann, D.C., and Lanning-Rush, J.L., 2017, *Methods for estimating annual exceedance-probability streamflows for streams in Kansas based on data through water year 2015 (ver. 1.1, September 2017)*: U.S. Geological Survey Scientific Investigations Report 2017–5063, 20 p., <https://doi.org/10.3133/sir20175063>.

Texas Water Development Board, *Lake Waco (Brazos River Basin)*, viewed on July 27, 2022, <https://www.twdb.texas.gov/surfacewater/rivers/reservoirs/waco/index.asp>

USACE, *HEC-RAS 2D Modeling User's Manual*, February 2016

USACE, *HEC-RAS Hydraulic Reference Manual*, February 2016

United States Department of Agriculture, *Chapter 5 of the NRCS National Engineering Handbook Part 630. Amended* May 2012.

USDA, NRCS, *Manning's n Values for Various Land Covers To Use for Dam Breach Analysis in Kansas*, 2016

USDA, NRCS, *NOAA Atlas 14 rainfall for Midwest and Southeast states*, 2015.

USDA, NRCS, *Part 630 National Engineering Handbook, Chapter 5 Streamflow Data*, March 2020

USGS Scientific Investigations Report 2009-5087, *Regression Equations for Estimation of Annual Peak-Streamflow Frequency for Undeveloped Watersheds in Texas Using an L-moment Based, PRESS-Minimized, Residual-Adjusted Approach*, June 2009

Appendix A BLE Map

